

EMG 45 ton power press

State	NEW
Category	Press
Brand	EMG
Model	45T
Serial number	-
Year of manufacture	-
Inventory number	100028



CHARACTERISTICS

With electro-pneumatic mono-disc clutch

Technical data

Adjustable stroke : from 6 to 100 mm
 Swan-neck depth : 220 mm
 Shut Height : 350 mm
 Stroke per minute : 130
 Press ram adjustment : from 0 to 70 mm

Standard equipment

Fixed frame
 6-digit counter with reset switch
 8-digit counter without reset switch
 Automatic lubrication with level control
 Bi-manual push-button safety control
 Stroke-by-stroke or continuous working
 Hydraulic unblocking system of the sliders
 Balancing system for the sliders
 Ejection bar in the press slider

COMPOSITION AND ACCESSORIES

Options (non-included)

Automatic vertical shield with pedal control
 SICK safety opto-electronic device : simple and double passage
 Pedal control for machine without movable shielding
 Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve
 Tilt table frame at 20° (hydraulic jack)
 Additional cam to collect information (feeder control, ...)
 Electronic cams Omron with 8 outlets
 Special selector for outside control (cycle departure outside of the press)
 6-digit counter pre-selector
 Fantini rubber cushion model PA/2ST : 60 mm stroke, 3-ton power at 6,5 bars with table plug, 80 mm thick, with 4 obrounds & 4 ejectors of 85 mm
 Worktable halogen lighting : 50W with 500 mm flex
 Worktable lighting : 2 neon tubes (18 W, only if Safety Opto-Electronic device)
 Variable speed drive with selection by potentiometer (380 V Tri)

Set of 2 anvil stakes DIN 508 M14 for T-grooves
 Set of 4 anti-vibration supports diameter 125 mm
 Lubricating kit (2 l pneumatic oil + 2 l lubricating oil)
 Band feeder - Straightener - Decoiler

