EMG 25 ton power press



State	NEW
Category	Press
Brand	EMG
Model	25T
Serial number	-
Year of manufacture	-
Inventory number	100027

CHARACTERISTICS

Adjustable stroke : from 5 to 75 mm
Swan-neck depth : 200 mm
Shut Height : 300 mm
Stroke per minute : 140
Press ram adjustment : from 0 to 60 mm

Standard equipment

20° tiltable frame
6-digit counter with reset switch
8-digit counter without reset switch
Centralised lubrication by hand pump
Bi-manual push-button safety control
Stroke-by-stroke or continuous working
Ejection bar in the press slider

COMPOSITION AND ACCESSORIES

Option (non-included)

Automatic vertical shield with pedal control
SICK safety opto-electronic device : simple and double passage
Pedal control for machine without movable shielding
Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve
Additional cam to collect information (feeder control, ...)
Variable speed drive with selection by potentiometer (220 V mono)
Exhaust pipe to decrease the sound level (2 dB)
Automatic lubrication with level control (normal use)
Automatic lubrication with level control (intensive use-outflow x 4)
Electronic cams Omron with 8 outlets
Special selector for outside control (cycle departure outside of the press)
6-digit counter pre-selector
Rubber cushion



Boulevard des Eplatures 37
CH-2300 La Chaux-de-Fonds

+41 (0)32 926 62 62
luthy@luthymac.ch