EMG 6 Ton power press



State	NEW
Category	Press
Brand	EMG
Model	6T
Serial number	-
Year of manufacture	-
Inventory number	100025

CHARACTERISTICS

Adjustable stroke: from 4 to 40 mm
Swan-neck depth: 120 mm
Shut Height: 200 mm
Stroke per minute: 240
Press ram adjustment: from 0 to 30 mm

Standard equipment

20° tiltable frame
6-digit counter with reset switch
8-digit counter without reset switch
Centralised lubrication by hand pump
Bi-manual push-button safety control
Stroke-by-stroke or continuous working
Ejection bar in the press slider

COMPOSITION AND ACCESSORIES

Options (non-included)

Automatic vertical shield with pedal control
Pedal control for machine without movable shielding
Unblocking wedge system for the slider at the dead bottom centre
Blower cam with magnetic sensor, solenoid valve 3/2 + tap locking valve
Additional cam to collect information (feeder control, ...)
Electronic cams Omron with 8 outlets
Special selector for outside control (cycle departure outside of the press)
6-digit counter pre-selector
Automatic lubrication with level control
Automatic lubrication with level control (intensive use-outflow x 4)
Rubber cushion
Worktable halogen lighting : 50W with 500 mm flex
Variable speed drive with selection by potentiometer (220 V mono)
Exhaust pipe to decrease the sound level (2 dB)
Metal sheet under press slider to collect oil (loss of 6 mm for clearance height)
Set of 2 anvil stakes DIN 508 M10 for T-grooves
Set of 4 anti-vibration supports diameter 80 mm .
Lubricating kit (2 l pneumatic oil + 2 l lubricating oil)
Band feeder - Straightener - Decoiler

Boulevard des Eplatures 37
CH-2300 La Chaux-de-Fonds
+41 (0)32 926 62 62
luthy@luthymac.ch



Boulevard des Eplatures 37
CH-2300 La Chaux-de-Fonds

+41 (0)32 926 62 62
luthy@luthymac.ch