EMG pneumatic press 8PHR



State	NEW
Category	Press
Brand	EMG
Model	8 PHR
Serial number	-
Year of manufacture	-
Inventory number	100016

CHARACTERISTICS

Adjustable stroke : from 0 to 100 mm
Swan-neck depth : 95 mm
Shut Height : from 40 to 260 mm
Strokes per minute : 40

VERSION 1

Machine delivered without any equipment and any control

VERSION 2

Bi-manual push-button safety control
Lateral protection panels
Distributor
Regulating and lubricating filter
Machine set on to its plinth, connected ready to work

VERSION 3 Version 2 with :

Pedal control to work protected tool (no risk for the operator)
Key-control selector
Machine fixed on to its plinth, connected ready to work

COMPOSITION AND ACCESSORIES

Options (non-included)

Base support 450 mm section to let legs through
Set of 2 lateral panels (only with based support) with 350× 250 mm as dimensions
5-digit mechanical counter with reset switch
Blocking of the press at dead bottom centre (control with the bimanual to go up and down)
Excess flow valve for descent speed regulation
Pause at dead bottom centre
Full set of filter & exhaust pipes to decrease level noise
Additional regulator to work with pressure under 3 bar (mini 0.5 bar)
Power regulator with needle pressure gauge : cycle repetition and 3 % precision
Power regulator with digital pressure gauge : cycle repetition and 1 % precision
Set of 2 anvil stakes for T groove M10
Set of 4 anti-vibration supports Ø 46
Maintenance kit
ER25 collet holder, with a collet chuck (2 to 16 mm Ø) and key of tightening
Parts quality system with force and displacement transducer



Boulevard des Eplatures 37
CH-2300 La Chaux-de-Fonds

+41 (0)32 926 62 62
luthy@luthymac.ch