EMG pneumatic press 1T



State	NEW
Category	Press
Brand	EMG
Model	1T
Serial number	-
Year of manufacture	-
Inventory number	100001

CHARACTERISTICS

Adjustable stroke : from 0 to 100 mm
Swan-neck depth : 100 mm
Shut height : from 140 to 200 mm
Strokes per minute : 35
VERSION 1

Machine delivered without any equipment and any control

VERSION 2

Bi-manual push-button safety control
lateral protection panels
Distributor
Regulating and lubricating filter
Machine fixed on to its plinth, connected ready to work

VERSION 3 Version 2 with :

Pedal control to work protected tool (no risk for the operator)
Key-control selector
Machine fixed on to its plinth, connected ready to work

COMPOSITION AND ACCESSORIES

Options (non-included)

Based support 450 mm section to let legs through
Set of 2 lateral panels, dimensions 350 x 250 (only with based support)
5-digit counter with reset switch
Bottom dead centre fine adjustment
Blocking of the press at dead bottom centre (control with the bimanual to go up and down)
Pause at dead bottom centre
Excess flow valve for descent speed regulation
Full set of filter & exhaust pipes to decrease level noise
Additional regulator to work with pressure under 3 bar (mini 0.5 bar)
Power regulator with needle pressure gauge : cycle repetition and 3 % precision (mini 0.5 bar)
Power regulator with digital pressure gauge : cycle repetition and 1 % precision (mini 0.5 bar)
Set of 2 anvil stakes for T groove M10
Set of 4 anti-vibration supports ? 46
Maintenance kit
ER25 collet holder, with a collet chuck (2 to 16 mm Ø) and key of tightening
Set of 4 rotating wheels with brake, for base support
Parts quality system with force and displacement transducer



WWW.LUTHYMAC.CH

Boulevard des Eplatures 37
CH-2300 La Chaux-de-Fonds

+41 (0)32 926 62 62
luthy@luthymac.ch